



EPDM
ROOF MEMBRANE

2 1/2"

1 1/4" GALV. RING SHANK NAIL
AT 12" ON CENTER

USE ADDITIONAL STAGGERED NAILS
IF FACE SIZE IS 8" OR LONGER

24 GA. GALV. CONTINUOUS CLEAT

DOES NOT NEED TO BE HAND CRIMPED

NOTES:

- MAXIMUM ANSI/SPRI ES1 TESTED FACE SIZE FOR 24 GA. GALV., 22 GA. GALV., AND .040 ALUMINUM IS 8"
- MAXIMUM ANSI/SPRI ES1 TESTED FACE SIZE FOR .050 AND .063 ALUMINUM IS 12"

MATERIAL: <input type="checkbox"/> 24 Ga. Galv. Steel <input type="checkbox"/> 22 Ga. Galv. Steel <input type="checkbox"/> .040" Aluminum <input type="checkbox"/> .050" Aluminum <input type="checkbox"/> .063" Aluminum	QUANTITY: ___ Lineal Feet (10' INCREMENTS) Color: _____ Finish: _____	ACCESSORIES: <input type="checkbox"/> Inside Miters <input type="checkbox"/> Outside Miters <input type="checkbox"/> Left Endcaps <input type="checkbox"/> Right Endcaps
---	---	---

PROJECT NAME:	QUOTE: <input type="checkbox"/>
	ORDER: <input type="checkbox"/> PO# _____

INSTALLER:	SIGNATURE

 AMERICAN ARCHITECTURAL METAL MANUFACTURERS, INC.	EAGLE PERIMETER EDGE SYSTEMS	ANSI/SPRI ES1 TALON LOK® GRAVEL STOP
---	-------------------------------------	---